

IMPACT

MULTIFUNCTIONAL FOR **1000** APPLICATIONS

ODORLESS PENETRATING FLUID AEROSOL

100 % PLANT-BASED

PENETRATING OIL, DEOXIDISING, LUBRICANT,
DEGREASER, TAR REMOVER
ANTI-CLOING, RELEASE AGENT,
RENEWING AGENT, SHINING AGENT



Nonfood Compounds
Program Listed H1
162700



RECOMMENDATION EU 84/2017
GUARANTEED WITHOUT HC,
WITHOUT MOSH/POSH,
WITHOUT MOAH

Highly lubricant, anti wear

Friction test (SRV):
0.12

Helps to reduce
energy
consumption,
disassembly effort
and operating noise
levels.

Strong penetratin g power

Low surface
tension: 23,4
Dynes/cm

Strong deoxidisin g power

Tested according to
MIL A 907 ED,
loosening torque
12Nm



Instant tar remover

Asphalt removal
test: 40 g at 20°C,
3'15"

**Unbundling for food
processing
industries
guaranteed without
HC,
without
MOSH/PO
SH,
without
MOAH.**

Analys report
available on
request

21/006838 LC
GC-FID DIN/EN
16995

Residual pesticides and genetically modified organism free

PHYSICO-CHEMICAL CHARACTERISTICS TYPICALS

PROPERTY	STANDARD	VALUE	UNITS
Appearance	Visual	Clear	-
Colour	Visual	Yellow	-
Odour	Olfactory	None	-
Density at 25°C	NF EN ISO 12185	0,930	kg/m ³
Refraction index	ISO 5661	1.4310	-
Freezing point	ISO 3016	- 22	°C
Water solubility	-	Partial, rinsable	%
Kinematic viscosity at 40°C	NF EN 3104	4.0	mm ² /s
Acid value	EN 14104	N/M	mg KOH/g
Iodine value	NF EN 14111	N/M	g I ₂ /100g

Water content	NF ISO 6296	50	ppm
Residue following rinsing with water	NF T 30-084	0	%
PERFORMANCE CHARACTERISTICS AS A DEGREASING SOLVENT			
PROPERTY	STANDARD	VALUE	UNITS
KB index	ASTM D 1133	180	-
Evaporation rate	-	N/A	min
Surface tension at 20°C	ISO 6295	23.4	Dyne/cm
Breakdown voltage	IEC 156	48	Volts
Copper blade corrosion, 100 h at 40°C	ISO 2160	1a	Class
PERFORMANCE CHARACTERISTICS AS A LUBRICANT			
PROPERTY	STANDARD	VALUE	UNITS
Potential noise reduction	GRW method	- 60	dB
FIRE SAFETY CHARACTERISTICS			
PROPERTY	STANDARD	VALUE	UNITS
Flash point (closed cup)	ISO 2719	> 100	°C
Autoignition temperature	ASTM E 659	> 230	°C
Lower explosive limit	NF EN 1839	1	% (volume)
Upper explosive limit	NF EN 1839	6	% (volume)
Content of explosive, oxidising, flammable, or very/extremely flammable substances	CLP regulation	0	%

TOXICOLOGICAL CHARACTERISTICS

PROPERTY	STANDARD	VALUE	UNITS
Anisidine value	NF ISO 6885	< 6	-
Peroxide value	NF ISO 3960	< 10	meq(O ₂)/kg
TOTOX (Anisidine index +2x Peroxyde index)	-	< 26	-
Content of CMR, irritant and corrosive substances	CLP regulation	0	%
Content of residual methanol derived from transesterification processes	GC-MS	0	%
Emissions of hazardous, CMR, irritant, corrosive compounds at 160°C.	GC-MS	0	%

ENVIRONMENTAL CHARACTERISTICS

PROPERTY	STANDARD	VALUE	UNITS
Water hazard	WGK Germany	1	Class
Primary biodegradability, CEC 21 days at 25°C	L 33 T 82	Higher than 90	%
Ready biodegradability OCDE 301 A over a 28-day period COD disappearance	ISO 7827	Higher than 80	%
Ready and ultimate biodegradability OCDE 310 C over a 28-day period Biodegradation after 69 days	Modified MITI	Higher than 90 100	% %

Bioaccumulation Partition index (n-octanol/water)	OCDE 107	Lower than 3	log KOW
Vapour pressure at 20°C	NF EN 13016-1	< 0.1	hPa
VOC concentration (Volatile Organic Compounds)	-	0	%
Sulphur content	Bomb calorimeter GC MS	< 200	ppm
Benzene content	ASTM D6229	0	%
Total halogen content	Bomb calorimeter GC MS	< 200	ppm
Chlorinated solvent content	-	0	
Aromatic solvent content	-	0	
Content of substances hazardous to the environment	CLP regulation	0	%
Content of compounds with non-zero GWP	-	0	%
Content of compounds with non-zero ODP	-	0	%
Carbon balance, life cycle analysis.	ISO 14040	4.57	Kg, carbon equivalent

* N/M: Not measured or non-measurable N/A: Not applicable

INSTRUCTIONS AND PRECAUTIONS OF USE

Use the appropriate nozzle for the job, shake the aerosol for a few seconds, spray on surfaces being treated. If needed, wipe with a damp cloth after treatment.

Looking for another product?

Discover our entire IAA range by clicking on the photo

